

Carbon Monoxide Alarm w/Display

EiA207DW



- ✓ UL2034 and CSA6.19 Certified
- ✓ Proven electrochemical sensor (10 year sensor life)
- ✓ LCD display provides additional information
- ✓ Unique plug-in Radio Module design
- ✓ Large EZ-Press™ Test/Hush button
- ✓ Automatic low battery status indication
- ✓ Automatic sensor fault indicator
- ✓ Built-in sounder – 85dBA at 3 meters
- ✓ End of life indication
- ✓ Power, alarm and fault indicator lights
- ✓ Memory feature indicates if CO has been previously detected
- ✓ Easy to install, twist-on base design
- ✓ 5 year Warranty

Product Description

The EiA207 series of Carbon Monoxide alarms has a high performance, proven electrochemical sensor to detect the presence of CO. Each sensor is individually calibrated & tested in Carbon Monoxide (CO) gas to ensure accuracy.


A unique external 8-pin header design enables simple, plug-in interface with a custom range (frequency and/or protocol) of radio modules.

The memory feature records the last CO alarm level and can be useful to check if CO has been present while the home owner or tenant was away from the property.

EiA207 devices are specifically designed for simple & intuitive, time-saving installation, commissioning and maintenance. All necessary mounting hardware is included.

The large, ergonomically located Test/Hush button enables full testing of the alarm. All aspects of the alarm (sensor, electronics, battery and sounder) can be tested with the press of a button.







The LCD displays CO level, status messages and icons.



Operation

- When toxic levels of Carbon Monoxide are detected, the alarm will sound and the red alarm LED will flash as detailed below:

CO Level	Red Led	Horn
< 70 ppm	Off	Off
> 70 ppm	1 flash every 3 sec	On within 60-240mins
> 150 ppm	2 flash every 3 sec	On within 10-50mins
> 400 ppm	3 flash every 3 sec	On within 4-15mins

- When in pre-alarm, the LCD will display a 'VENTILATE'  message and when in full alarm it will display an 'EVACUTE'  message.
- The device will automatically cease to alarm when the carbon monoxide gas clears.
- On 'END-OF-LIFE' , sensor fault , or 'LOW BATTERY' condition ; the amber LED will flash and the sounder will beep twice every 50 seconds.
- If a low battery is detected the LCD will display a 'LOW BATTERY'  warning and the amber and green LEDs will flash once every 50 seconds.
- Pressing and holding the 'TEST/HUSH' button will perform a complete device test as well as beeping to verify functionality.

Technical Specification

Sensor:	Proven electrochemical sensing technology. 100% calibrated and tested with carbon monoxide gas to ensure accuracy. CO level is checked every 4 seconds.
Radio Intergration:	Plug-in; 8 Pin header
Integrated head removal tamper switch:	When the sensor head is removed a signal can be sent to the panel via the RF module
Test/Hush button operation:	<ul style="list-style-type: none"> • Pressing and holding the Test/Hush button will initiate a test of the sensor, electronics, battery and sounder • Briefly pressing the Test/Hush button will 'Hush' (silence) the sounding alarm • As a safety feature, the 'Hush' function will automatically be disabled if the level of carbon monoxide gas detected is greater than 150ppm
Batteries:	(2) AAA Batteries
Display:	24mm x 20mm / .85" x .71" passive LCD display
Display Range:	30ppm to 995ppm in 5ppm intervals
LED indications:	<ul style="list-style-type: none"> • Power-up & Test: Green LED lights • Alarm: Red LED lights • Fault: Amber LED lights • Test / Diagnostic: Red, Amber & Green LED's light
End-of-Life Indicator:	The CO Alarm includes an 'end-of-life' indicator which will notify the user when the device has reached the end of its 10 year operational life and needs to be replaced
Alarm:	Bult-in piezoelectric horn
Alarm Sound Output:	85dBA at 3m
Temperature:	0 to 40°C / 32 to 104°F (Operating), 0 to 35°C / 32 to 95°F (Storage)
Humidity Range:	15% to 95% non-condensing
Dimensions:	120 mm x 105 mm x 45 mm / 4.72" x 4.13" x 1.77"
Weight:	180 grams / 6.35 ounces
Approvals:	UL 2034 & CSA6.19 approved. Manufactured to ISO 9001:2000 quality standards.
Warranty:	5 year (limited) warranty

*Specifications are subject to change

Ordering information	Product	Short Description
	EiA207DW-1XUS	CO Alarm, Plain Box
	EiA207DW-0AUS	CO Alarm, Bulk pack 20